

Schedule No. CA-Compound Meters
California American Water
COMPOUND METERS

APPLICABILITY

Applicable to all service.

TERRITORY

All territories served by California American Water Company

RATES

Detailed rates to be provided as part of the proposed decision for each district, but in general the total flow of all meters should be used to find the closest flow of a single larger meter. And when deciding between two meter flows, use the lower flow meter, which would result in a lower charge to the customer. For example, consider that a 1.5" inch meter flows 100 gpm. Therefore two, 1.5" meters flow 200 gpm. Given that total flow, the nearest total equivalent flow is either a 2" meter (160 gpm) or a 3" meter (450 gpm). The charge should be rounded down to the customer benefit.

Meter Battery Accounts—flows

<u>Meter size</u>	<u>Average flow at 100% accuracy</u>
5/8"	20 gpm
3/4"	30 gpm
1"	50 gpm
1 1/2"	100 gpm
2"	160 gpm
3"	450 gpm
4"	1,100 gpm
6"	2,300 gpm
8"	4,000 gpm
10"	7,250 gpm

(TO BE INSERTED BY UTILITY)

ADVICE LETTER NO. 1072-B

ISSUED BY

D. P. STEPHENSON

NAME

(TO BE INSERTED BY C.P.U.C.)

DATE FILED JUN 22 2015

EFFECTIVE APR 30 2015

DECISION NO. D.15-04-007

DIRECTOR - Rates & Regulatory

TITLE

RESOLUTION _____